

LUPIN BF3-NP

NEUTRON REM COUNTER FOR PULSED FIELDS







Modular electronics, high sensitivity

From thermal up to 10 GeV or up to 20 MeV (LITE)

Energy response fitting ICRP74 conversion curve

Unaffected by signal pile-up

Max H*(10) per burst in pulsed fields: 2 µSv

Excellent gamma rejection (< 0.5 μSv/h @ 50 mSv/h)

Connectable to a SATURN





Only active detector worldwide efficiently working in PF Fully customizable for specific requirements

LUPIN BF3-NP is an environmental monitoring unit for neutron $H^*(10)$ measurements, with unique excellent performance for neutron detection in pulsed fields.

The rem counter is composed of:

- BF₃ proportional counter
- Cylindrical moderating assembly

• Built-in power supply, signal management and control electronics

The electronics processes the signal coming from the detector and elaborates the instantaneous H*(10) rate value every second.

If required, the radiation sensitive electronics can be housed in a separate rack. An accessory IP54 version is also available

Data are sent to the connected SATURN ratemeter acquisition and control unit, which locally displays the instantaneous $H^*(10)$ rate and the integrated values and compares them to the pre-set alarm thresholds.

A **LUPIN BF3-NP LITE** version is also available, featuring a lighter build and a narrower energy range, suitable for all the applications that do not require to detect neutrons with energy above 20 MeV.

Papers published in international scientific journals:

- M. Caresana, M. Ferrarini, G.P. Manessi, M. Silari and V. Varoli, LUPIN, a new instrument for pulsed neutron fields, Nuclear Instruments and Methods in Physics Research Section A 712 (2013) 15-26.
- M. Caresana, C. Cassell, M. Ferrarini, E. Hohmann, G.P. Manessi, S. Mayer, M. Silari and V. Varoli, A new version of the LUPIN detector: improvements and latest experimental verification, Review of Scientific Instruments 85 (2014) 065102.

TECHNICAL SPECIFICATIONS

General characteristics

- Temperature range: 0° ÷ 50 °C
- Dimensions: Ø = 250 mm, H = 425 mm
- Weight: 18 kg; 15 kg (LITE version)
- Cylindrical BF₃ detector, 0.26 atm
- Energy range:
 - from 0.025 eV to 10 GeV (standard version)
 from 0.025 eV to 20 MeV (LITE version)
- H*(10) rate range: from 10 nSv/h to 100 mSv/h
- Max H*(10) per burst in pulsed fields with underestimation \leqslant 10%: 2 μSv
- Neutron sensitivity: 0.6 cps/ μ Sv/h
- Gamma sensitivity: < 0.5 µSv/h at 50 mSv/h, 662 keV
- Angular dependence: < 20%

Built-in electronics

- Watchdog: good functioning circuit control
- Available communications: serial RS232 (default), serial for long distance RS485/422, Ethernet up to 1 km

OPTIONS

- Lighter version and narrower energy range (LITE version)
- Radiation sensitive electronics installed in a separate rack
- Ultra-fast response (alarm signal in 50 ms): dual use as
- neutron rem counter beam loss monitor

ACCESSORIES AVAILABLE UPON REQUEST

- Traceable calibration
- Trolley kit: bare/unwired trolley for wheeled transport
- IP54 configuration
- Flight case
- Warranty extension from 12 months to 24 months



LUPIN BF3-NP performance in neutron pulsed fields (from: "A new version of the LUPIN detector", Rev. Sci. Instrum. 85, 065102, 2014)



© ELSE NUCLEAR Sr





LUPIN rem counters response function VS ICRP

Operative HQ: Via Dante Alighieri, 16 - 21052 Busto Arsizio, Varese – Italy +39 0331 620533 - info@elsenuclear.com